

SUPERArmor FRP Ballistic Panel

Technical Data Sheet



*UL 752 LEVEL 3 Compliant
Tested by United States Test Laboratory*

The Ultimate Panel for Ballistic and Fragmentation Protection

FEATURES AND BENEFITS

- UL 752 Level III Compliant
- Light Weight
- Easy to Install
- Corrosion Resistant

SUPERArmor FRP Ballistic Panels are designed for protection in various government and commercial applications. SUPERArmor panels are available in 4' x 8' sheets, are approximately 1/2" thick and weigh approximately 160 lbs. These panels are light weight, easily installed using standard hand tools and painted to improve aesthetics.

TYPICAL APPLICATIONS

- Asset Hardening (walls and roof)
- Court Room Protection
- Banks
- Safe Rooms
- Storm Shelters

TEST RESULTS

SuperArmor was tested in accordance with the specification requirements for ballistic panels and comply with UL 752 Level III ballistic panel specifications*. Test results are available upon request.

*Tested by United States Test Laboratory

Contact us today at 888-CPI-PULL(274-7855) so we can provide with a solution to your protection needs!

Flowgrip® and Pultex® are registered trademarks of Creative Pultrusions, Inc. Creative Pultrusions™, Shaping the Future™, Superstud!™, Superstud!™/Nuts!, Superstik™, SUPURTUF™, Superplank™, Superdeck™, Supergrate™, Tuf-dek™, SuperLoc™, SuperWale™, SuperCap™, SuperRod™, Pultrusion Dynamics™, DYNAPUL™, Pulshaping™, TOPSCAN™ and TOPDIE™ are trademarks of Creative Pultrusions, Inc.

*ISOPLAST is the trademark of The Dow Chemical Company

Creative Pultrusions, Inc. reserves the right to edit and modify literature, please consult the web site for the most current version of this document.



214 Industrial Lane, Alum Bank, PA 15521
839.4186 • Fax 814.839.4276 • Toll Free 888.CPI.PULL
www.creativepultrusions.com

CPM013-1007.1C
DLR: 07.02.13