

Product/Chemical #: Pultruded Fiberglass Grating with Anti-Slip Surface

Date of Preparation: 2/16/2016



CREATIVE PULTRUSIONS, INC.

214 Industrial Lane, Alum Bank, PA 15521
814.839.4186 · Fax: 814.839.4276 · Toll free 888.CPI.PULL
Email: crpul@pultrude.com · www.creativepultrusions.com

Safety Data Sheet

Product/Chemical #: Pultruded Fiberglass Grating with Anti-Slip Surface

Date of Preparation: 2/16/2016

Section 1 – Materials and Company Identification

Product/Chemical Name: Fiberglass Reinforced Thermoset Polymerized Resin Composite with Crystalline Silica Sand(quartz) Anti-Slip Surface

Trade Name: Supergrate®

General Use: Structural Component

Manufacturer: Creative Pultrusions, Inc., 214 Industrial Lane, Alum Bank, PA 15521-8304

PHONE (814) 839-4186, FAX (814) 839-4276 (8AM – 4:30PM EST)

24 Hour Emergency Phone Number: (814) 839-4186

Section 2 – Hazards Identification

As manufactured this product is considered non-hazardous. Product will form dust and particulate matter when drilling, grinding, cutting or sanding. Dust is combustible. Any dust containing silica sand is considered hazardous under the OSHA Hazardous Communication Standard.

Acute Effects

Inhalation: Nuisance dust from machining can cause irritation.

Eye: Nuisance dust from machining can cause irritation.

Skin: Nuisance dust from machining can cause irritation.

Ingestion: N/A

Chronic Effects

Inhalation: The prolonged and repeated inhalation of respirable crystalline silica can cause silicosis.

Carcinogenicity: Respirable crystalline silica is classified as carcinogenic to humans

Medical Conditions Aggravated by Long-Term Exposure: None as manufactured.

Section 3 – Material Composition and Information on Ingredients

<u>Ingredient Name</u>	<u>CAS Number</u>	<u>Percent by Weight</u>
Polymerized Resin Mixture	None	25%-45%
Fiberglass	659997-17-3	55%-75%
Crystalline Silica (quartz)	14808-60-7	0% - 4%

Product/Chemical #: Pultruded Fiberglass Grating with Anti-Slip Surface

Date of Preparation: 2/16/2016

Section 4 – First Aid Measures

Inhalation: Remove from dust to fresh air.

Eye Contact: Flush with water or eye rinse.

Skin Contact: Wash with soap and cold water.

Ingestion: NA

If condition persists, get appropriate in-plant medical support or consult physician.

Section 5 – Fire Fighting Measures

Flash Point: 675F (dust)

Extinguishing Media: Water, Foam, Type A, B, or C extinguishers

Unusual Fire or Explosion Hazards: Do not expose fine dust to an ignition source.

Hazardous Combustion Products: Heavy Smoke, CO, CO₂, and irritating or toxic vapors and gases

Fire-Fighting Instructions: Use self-contained breathing apparatus

Section 6 – Accidental Release Measures

The product as manufactured is non-hazardous. In areas where drilling, grinding, cutting or sanding occurs on this product, care should be taken to clean up dust. Dust deposits should not be allowed to accumulate on surfaces. Dust is considered a St 1 class dust with a Kst (bar-m/s) of less than 100. Avoid dispersal of dust with compressed air.

Section 7 – Handling and Storage

Minimize dust generation and accumulation through routine housekeeping to ensure that dusts do not accumulate on surfaces. Keep airborne dust concentrations below permissible exposure limits.

Protective gloves are recommended for handling material comfortably. Long sleeved shirts and pants minimize exposure to dust.

Section 8 – Exposure Controls/Personal Protection

Component	CAS	Percent	ACGIH TLV	OSHA PEL	Units
Polymerized Polyester Resin Mixture	None	25%-55%	Not Established	Not Established	Not Established
Fiberglass	659997-17-3	45%-75%	Not Established	Not Established	Not Established
Inert or Nuisance dust	None	NA	10	15	mg/m ³
Crystalline Silica (quartz)	140808-60-7	0% - 4%	.025	10/%SiO ₂ +2	mg/m ³

Engineering Controls / Ventilation: Must comply with NFPA 68

Respiratory Protection: None required if dust is not present. Keep airborne dust concentrations below permissible exposure limits. When dust exposures have the potential to exceed regulated values, a NIOSH approved dust mask must be used.

Eye Protection: Safety glasses with side shields or goggles.

General: Safety Glasses, Gloves, long sleeved shirts and pants recommended.

Product/Chemical #: Pultruded Fiberglass Grating with Anti-Slip Surface

Date of Preparation: 2/16/2016

Section 9 – Physical and Chemical Characteristics

Appearance: Various colors and shapes structural profiles

Odor: No significant odor

pH: N/A

Melting Point/Freezing Point: N/D

Initial Boiling Point: N/A

Flash Point: N/A

Evaporation Rate: N/A

Flammability: N/D

Upper/Lower Explosion Limit: N/A

Vapor Pressure: N/A

Vapor Density: N/A

Specific Gravity (H₂O)=1, at 4° C: 1.61-2.0

Solubility: N/A

Partition Coefficient: N/A

Auto-Ignition Temperature: N/D

Decomposition Temperature: N/D

Viscosity: N/A

Section 10 – Stability/Reactivity

Stability: Product is stable.

Polymerization: Hazardous polymerization will not occur.

Conditions to avoid: Extreme heat, sources of ignition and flames.

Incompatibilities: Do not store with strong oxidizing agents. Do not expose crystalline silica to hydrofluoric acid, fluorine, chlorine trifluoride, or oxygen difluoride.

Hazardous decomposition products: Heavy Smoke, CO, CO₂, and irritating or toxic vapors and gases.

Section 11 – Toxicological Information

No toxicological test data is available for this product as manufactured. This product does contain crystalline silica. Repeated and prolonged exposures to dust containing crystalline silica can cause silicosis, cancer and autoimmune diseases.

Section 12 – Ecological Information

No ecotoxicity test data is available for this product. This product is not expected to present a hazard to aquatic and terrestrial environments.

Section 13 – Disposal Considerations

As supplied this product is non-hazardous. Consult federal, state and local regulations for proper disposal.

Section 14 – Transport Information

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Not Regulated

Shipping Symbols: N/A

Hazard Class: Not Hazardous

ID No.: N/A

Packing Group: Not Determined

Label: Not Required

Special Provisions (172.102): None

Product/Chemical #: Pultruded Fiberglass Grating with Anti-Slip Surface

Date of Preparation: 2/16/2016

Section 15 – Regulatory Information

TSCA Inventory: All ingredients are on the TSCA inventory.

SARA Section 313: None above de minimus quantity.

SARA 311/312: None as supplied.

OSHA Hazardous Communication Categories: Dust is combustible and an irritant. Dust containing respirable crystalline silica is considered hazardous under the OSHA Hazardous Communication Standard.

Canada-WHMIS Classification: Non-hazardous

Section 16 – Other Information

Refer to NFPA 654, standard for the prevention of fire and dust explosion from the manufacturing, processing and handling of combustible particulate solids, for safe handling of dusts generated during processing.

N/D - Not Determined.

N/A – Not Applicable

Prepared By: Ronald W. Allison

Last Revision: 03.10.17

Disclaimer: While the information and recommendations set forth in the SDS are believed to be accurate as of the date of the SDS preparation, Creative Pultrusions, Inc. makes no representation or warranty, direct or indirect, regarding their accuracy or completeness nor do we assume any obligations to advise you of any modifications or corrections to or of such information and recommendations of which we may become aware from the date hereof. Recipients are advised to confirm as they may deem acceptable that the information and recommendations are current and applicable to meet their requirements. Since the conditions are methods of use of this product are beyond our control, Creative Pultrusions, Inc. disclaims any and all liability arising out of the use of this product or the information provided herewith.